

INTERNATIONAL SERIES LASER-RADAR DETECTOR

GT-435Xi



Order Number GT-435Xi
MSRP \$139.95
Unit Dimensions 1.35 in. H x 2.84 in. W x 4.41 in. L
Unit Weight 5.6 oz.
Packaging Box
Retail Packaging Dimensions 6.06 in. H x 7.81 in. W x 2.25 in. D
Retail Weight 14.4 oz.
UPC 0 52303 40582 2
Case Pack Quantity 6
Case Pack Dimensions 6.38 in. H x 7.81 in. W x 13.625 in. L
Case Pack Weight 3 lbs.
Case Cube .38
Accessories Windshield Bracket Kit, Power Cord, Manual

Whistler laser-radar detectors receive laser guns that operate at a laser wavelength of 800-1000nm.

Whistler detectors receive the following radar frequencies:

10.500 - 10.550 GHz X Band
24.050 - 24.250 GHz K Band
33.400 - 36.000 GHz SuperWideBand Ka
34.000, 34.300 GHz Ka Narrow

This includes the POP™ instant-on feature, which operates within the K and Ka bands. POP™ is a trademark of MPH Industries.

One or more U.S. patents may apply:
#5,666,120, #7,215,276



www.whistlergroup.com | 479.273.6012

©2012 The Whistler Group, Inc.
3604 NW Frontage Road | Bentonville, AR 72712

FEATURES:

RED OLED TEXT DISPLAY provides better contrast, brightness and color. Shows alerts detected, engaged modes and digital signal strength in text format (i.e. HIGHWAY or Ka9).

Ka NARROW MODE looks only for the following Ka Frequencies: 34.0 GHz and 34.3 GHz

DETECTS EUROPEAN LASER GUNS (Traffipatrol XR, Riegl, Jenoptik, Laveg, Truspeed and more)

SELECTABLE LASER MODES allow selection of multiple pulse rate segments including **TRAFFIPATROL XR**, **LISD**, and laser guns with **STEALTH MODES**

X/K FILTER MODES offer multiple levels of rejection to reduce false alerts caused by Radar Traffic Monitoring Systems including radar based lane change assistant

Ka FILTER MODES offer multiple levels of signal processing to reduce false alerts caused by some radar detectors

WHISTLER EXCLUSIVE LASER SIGNATURE ID (LSID)

Laser Identifier indicates the Pulses Per Second (PPS) transmitted by Speed Laser or other forms of laser sources.

POP™ MODE DETECTION advanced speed detection capability responds to brief bursts of radar

ALERT PERISCOPES LED's on top of the unit provide additional visual alert

SELECTABLE TONE ALERTS allow choice of tones providing distinct audible alerts for bands received

360° MAXX COVERAGE detects from front, sides, and rear

3 CITY MODES (City, City 1, City 2) reduce the annoyance of false alerts

HIGH GAIN LENS provides increased field of view which means better range

STAY ALERT® Whistler's exclusive feature that tests your alertness on long trips

DIM / DARK MODE reduces the illumination of the display. When in dark mode, the display is turned off during an alert then remains off for 20 more seconds before returning to its dimmer setting.

QUIET / AUTO QUIET MODE silences audio alerts

ALERT PRIORITY displays most important signal when more than one is detected

SETTING SAVER saves personalized settings when unit is turned off

SELECTABLE VEHICLE BATTERY SAVER allows you to customize the automatic shut down feature

VG-2 DETECTION when engaged, alerts to VG-2 when detected



WHISTLER